
# **BookletChart**

# Lake Wimico To East Bay

(NOAA Chart 11393)



A reduced scale NOAA nautical chart for small boaters. When possible, use the full size NOAA chart for navigation.


- ☑ Complete, reduced scale nautical chart
- ✓ Print at home for free
- ☑ Convenient size
- ☑ Up to date with all Notices to Mariners


NOAA

Home Edition (not for sale)

☑ United States Coast Pilot excerpts

✓ Compiled by NOAA, the nation's chartmaker.





#### What are Nautical Charts?

Nautical charts are a fundamental tool of marine navigation. They show water depths, obstructions, buoys, other aids to navigation, and much more. The information is shown in a way that promotes safe and efficient navigation. Chart carriage is mandatory on the commercial ships that carry America's commerce. They are also used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters.

#### What is a BookletChart<sup>™</sup>?


This BookletChart is made to help recreational boaters locate themselves on the water. It has been reduced in scale for convenience, but otherwise contains all the information of the full-scale nautical chart. The bar scales have also been reduced, and are accurate when used to measure distances in this BookletChart. See the Note at the bottom of page 5 for the reduction in scale applied to this chart.

Whenever possible, use the official, full scale NOAA nautical chart for navigation. Nautical chart sales agents are listed on the Internet at <a href="http://www.NauticalCharts.NOAA.gov">http://www.NauticalCharts.NOAA.gov</a>.

This BookletChart does NOT fulfill chart carriage requirements for regulated commercial vessels under Titles 33 and 44 of the Code of Federal Regulations.

#### **Notice to Mariners Correction Status**

This BookletChart has been updated for chart corrections published in the U.S. Coast Guard Local Notice to Mariners, the National Geospatial Intelligence Agency Weekly Notice to Mariners, and, where applicable, the Canadian Coast Guard Notice to Mariners. Additional chart corrections have been made by NOAA in advance of their publication in a Notice to Mariners. The last Notices to Mariners applied to this chart are listed in the Note at the bottom of page 7. Coast Pilot excerpts are not being corrected.



[Coast Pilot 5, Chapter 6 excerpts]
(114) St. Joseph Bay is separated from the Gulf by St. Joseph Peninsula (St. Joseph Spit) a long, narrow strip of land and sand hills. St. Joseph Bay, recognized as one of the best harbors on the Gulf, is easily entered by vessels with drafts to 25 feet except during periods of very severe weather such as hurricanes. St. Joseph Bay Entrance
Lighted Buoy 2 marks the entrance.
(115) Port St. Joe is on the E shore of St. Joseph Bay. A large paper mill on the

waterfront and two chemical plants on Gulf County Canal furnish the main industry for the town. Waterborne commerce consists mainly of paper, marine supplies, petroleum products, and chemical products. (117) **Prominent features.** The stack and buildings of the papermill and the chemical plant are the most prominent objects visible from the Gulf. Several water tanks are conspicuous at a closer distance inshore.

(119) A sunken wreck was reported in the safety fairway in about 29°50.2'N., 85°41.6'W.

(120) A fish haven with an authorized minimum depth of 34 feet is close off the SE side of the entrance to the Port St. Joe Safety Fairway. (122) **Channels.** From the Gulf, the dredged channel leads across 18-foot shoals to the deeper water inside. Federal project depths are 37 feet to a point about 0.5 mile N of St. Joseph Point, thence 35 feet to Harbor Channel and to a turning basin immediately to the W, thence 35 feet to South Channel, thence 27 feet in South Channel; project depth in the turning basin is 32 feet. A shoal tends to build E from the extremity of St. Joseph Point into the W side of the entrance channel. South Channel is no longer maintained.

(123) The channels, except for South Channel, are marked by lights and buoys; lighted ranges mark the entrance channel and North Channel. Port St. Joe Entrance Channel lighted range on top of the paper mill is often difficult to see because of the steam from the mill.

(124) A swash channel with a depth of 14 feet follows the shore of **St. Joseph Point** at a distance of 0.2 mile and passes between the shore and a shoal that has a depth of about 8 feet. The channel is subject to changes and should be used only with local knowledge.

(125) **Gulf County Canal** provides a connection between St. Joseph Bay and the Intracoastal Waterway. The canal has a Federal project depth of 12 feet.

(126) Anchorages. Vessels should anchor in Port St. Joe Anchorages, N and S of the Safety Fairway leading to the entrance channel. Depths of 24 to 37 feet with hard sand or hard mud bottom are available throughout most of the interior part of the bay. The S third of the bay, a shelf along the sides, and several spoil areas along the entrance channel and along the E side of St. Joseph Peninsula are shoal. Shoaling to 11 feet is close N of South Channel centered in about 29°48'37"N., 85°19'43"W.

(128) **Currents.** Strong and erratic crosscurrents are reported at the entrance to St. Joseph Bay NE of St. Joseph Point. These currents are reported to be particularly strong during the ebb. Caution is advised when entering the bay.

Explosives anchorages are in St. Joseph Bay.

(129) **Pilotage, Port St. Joe.** Pilotage is compulsory for all foreign vessels and U.S. vessels under register in foreign trade if drawing more than 7 feet of water. Pilotage is optional for U.S. coastwise vessels that have on board a pilot licensed by the Federal Government. Vessels should be prepared to proceed to the entrance to St. Andrew Bay, if so directed where the pilot will board between St. Andrew Bay Entrance Lighted Whistle Buoy SA and the first set of entrance channel buoys in about 30°06.8'N., 85°44.5'W.

(134) **Harbor regulations.** The **harbormaster** can be reached by telephone (904-227-1319). A **speed limit** of 4 m.p.h. is posted in the harbor

(138) **Small-craft facilities.** A boat basin on the N bank of the Gulf County Canal just NE of the highway bridge provides berths, gasoline, diesel fuel, water, ice, and marine supplies.

(140) **Bell Shoal** is the broken ground NW of the entrance channel making off from St. Andrew Point, 6.5 miles NW of St. Joseph Point. (141) **Mexico Beach** is a small resort community 4.5 miles N of St. Joseph Point. A privately marked channel leads to **Salt Creek**; the entrance is subject to shoaling and should not be attempted without local knowledge. The entrance to the creek was closed to navigation. The depths inside the creek were 5 feet. U.S. Route 98 bridge, on the E branch of the creek 0.3 mile above the entrance, has a clearance of 13 feet. Several small marinas are on the E branch above the bridge. Berths with water and electricity, gasoline, ice, and marine supplies are available. A no-wake **speed limit** is enforced on Salt Creek. (142) **Crooked Island** encloses **St. Andrew Sound**, a shallow, unimportant body of water.

(143) A **restricted area** of a drone launch corridor extends through St. Andrew Sound into the Gulf of Mexico.

#### **Table of Selected Chart Notes**

Nov. /05

Nov. /05



#### HEIGHTS

Heights in feet above Mean High Water.

#### INTRACOASTAL WATERWAY AIDS

The U.S. Aids to Navigation System is designed for use with nautical charts and the exact meaning of an aid to navigation may not be clear unless the appropriate chart is con-

sulted.

Aids to navigation marking the Intracoastal Waterway exhibit unique yellow symbols to distinguish them from aids marking other

waterways. When following the Intracoastal Waterway westward from Carrabelle, Florida to Brownsville, Texas, aids with yellow frangles should be kept on the starboard side of the vessel and aids with yellow squares should be kept on the port side of the vessel. A horizontal yellow band provides no lateral information, but simply identifies aids to navigation as marking the Intracoastal Waterway.

#### CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

#### INTRACOASTAL WATERWAY

Project Depths

12 feet Carrabelle, Fla. to Brownsville,

Texas.
The controlling depths are published periodically in the U.S. Coast Guard Local Notice

The Waterway is indicated by a magenta line. Mileage distances shown along waterway are in Statute Miles, based on zero at Harvey Lock, La, and are indicated thus:

Tables for converting Statute Miles to International Nautical Miles are given in U.S. Coast Piller 5.

#### NOTE A

NOTE A
Navigation regulations are published in
Chapter 2, U.S. Coast Pilot 5, Additions or
revisions to Chapter 2 are published in the
Notices to Mariens: Information concerning
the regulations may be obtained at the Office
of the Commander, 8th Coast Guard District in
New Orleans, Louislana, or at the Office of the
District Engineer, Corps of Engineers in Mobile,
Alabama

Refer to charted regulation section numbers.

All craft should avoid areas where the skin divers flag, a red square with a diagonal white stripe, is displayed.

For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans over the charge! over the channel.

#### AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to

#### RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

#### CAUTION

Small craft should stay clear of large commercial and government vessels even if small craft have the right-of-way.

Limitations on the use of radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117.
Radio direction-finder bearings to commercial

broadcasting stations are subject to error and should be used with caution.

Station positions are shown thus ⊙(Accurate location) o(Approximate location)

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 5 for important supplemental information.

#### POLLUTION REPORTS

Report all spills of oil and hazardous sub-stances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

#### HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which is North American Datum of 1983 (MD B3), which for charling purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.739 northward and 0.282" eastward to agree with this chart.

PLANE COORDINATE GRID

(based on NAD 1927)
Florida State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus:
The last three digits are omitted.

Corrected through NM Nov. 12/05, LNM Nov. 08/05

Corrected through NM Nov. 12/05, LNM Nov. 08/05

#### WARNING /

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

#### CAUTION

#### WARNINGS CONCERNING LARGE VESSELS

WARNINGS CONCERNING LARGE VESSELS
The "Rules of the Road" state that recreational boats
shall not impede the passage of a vessel that can
navigate only within a narrow channel or fairway. Large
size but actually transit at speeds in excess of 12 knots,
requiring a great distance in which to maneuver or stop.
A large vessel's superstructure may block the wind with
the result that sailboats and sailboards may unexpectedly
find themselves unable to maneuver. Bow and stern
waves can be hazardous to small vessels. Large vessels
may not be able to see small craft close to their bows.

#### HURRICANES AND TROPICAL STORMS

Hurricanes, tropical storms and other major storms may cause considerable damage to marine structures, aids to navigation and moored vessels, resulting in submerged debris in unknown locations.

Charted soundings, channel depths and shoreline may not Charted soundings, channel depths and shoreline may not reflect actual conditions following these storms. Fixed aids to navigation may have been damaged or destroyed. Buoys may have been moved from their charted positions, damaged, sunk, extinguished or otherwise made inoperative. Mariners should not rely upon the position or operation of an aid to navigation. Wrecks and submerged obstructions may have been displaced from charted locations. Pipelines may have become uncovered or moved.

or moved.

Mariners are urged to exercise extreme caution and are requested to report aids to navigation discrepancies and hazards to navigation to the nearest United States Coast Guard

COLREGS: International Regulations for Preventing Collisions at Sea, 1972

Additional information can be obtained at nauticalcharts.noaa.gov.

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

#### NOTE S

NOIES

Regulations for Ocean Dumping Sites are contained in 40 CFR, Parts 220-229.
Additional information concerning the regulations and requirements for use of the sites may be obtained from the Environmental Protection Agency (EPA). See U.S. Coast Plots appendix for addresses of EPA offices. Dumping subsequent to the survey dates may have reduced the depths shown.

#### **FACILITIES**

Locations of public marine facilities are shown by large magenta numbers with leaders and refer to the facility tabulation

#### PUBLIC BOATING INSTRUCTION PROGRAMS

The United States Power Squadrons (USPS) and U.S. Coast Guard Auxiliary (USCGAUX), national organizations of boatmen, conduct extensive boating instruction programs in communities throughout the United States. For information regarding these educational courses, contact the following sources:

USPS - Local Squadron Commander or USPS Headquarters, 1504 Blue Ridge Road, Raleigh, NC 27607, 888-367-8777

USCGAUX - COMMANDER (OAX), Eighth Coast Guard District, Hale Boggs Federal Building, Suite 1126, 500 Poydras Street, New Orleans, LA 70130, 800-524-8835 or USCG Headquarters, Office of the Chief Director (G-OCX), 2100 Second Street, SW, Washington, DC 20593

#### CAUTION

This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner.

	Height re	ferred to datun	n of soundings	(MLLW)
Place	Mean Higher High Water	Mean High Water	Mean Low Water	Extreme Low Water
Port Saint Joe,	feet	feet	feet	feet
St. Joseph Bay	1.4	-	-	-2.0
Farmdale, East Bay	1.6	-	-	-2.0
Wetappo Creek, East Bay	1.4	-	-	-2.0
Note: In the Intracoastal Periodic Tide has a mear				reek the

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.

Aids to Navigation (lights	are white unless	otherwise indicated):		
AERO aeronautico	ol G gree	n	Mo morse code	R TR radio towe
Al alternating	IQ inte	rrupted quick	N nun	Rot rotating
B black	Iso iso	ohase	OBSC obscured	s seconds
Bn beacon	LT HO	lighthouse	Oc occulting	SEC sector
C can	M naut	ical mile	Or orange	St M statute mile
DIA diaphone	m minu	ites	Q quick	VQ very quick
F fixed	MICRO	TR microwave tower	R red	W white
FI flashing	Mkr mo	ırker	Ra Ref radar reflec	tor WHIS whistle
-			R Bn radiobeacon	Y yellow
Bottom characteristics:				
Blds boulders	Co coral	gy gray	Oys oysters	so soft
bk broken	G gravel	h hard	Rk rock	Sh shells
Cy clay	Grs grass	M mud	S sand	sy sticky
Miscellaneous:				
AUTH authorized	Obstn	obstruction F	D position doubtful	Subm submerged
ED existence doub	otful PA pos	ition approximate F	Rep reported	

#### MERCATOR PROJECTION, SCALE 1:40,000 AT LAT. 29°50' SOUNDINGS IN FEET AT MEAN LOWER LOW WATER NORTH AMERICAN DATUM OF 1983 (WORLD GEODETIC SYSTEM 1984)

PORT ST. JOE HARBOR CHANNEL DEPTHS TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - REPORT OF JUL 2009													
CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW) PROJECT DIMENSIONS													
	NAME OF CHANNEL	LEFT OUTSIDE QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (NAUT. MILES)	DEPTH MLLW (FEET)					
	RT ST. JOE HARBOR	25.9	30.7A	30.5B	5,6,7-09	300-500	8.0	35-37					
_	IORTH CHANNEL	24.7	25.3	25.1	5,0,7-09	300-500	4.1	35					
	URNING BASIN	25.8	25.2	24.7	5-09	650	0.3	32					
	HARBOR CHANNEL	25.6	25.6	25.8	5-09	250	0.3	35					

#### PRINT-ON-DEMAND CHARTS

NOAA and its partner, OceanGraftix, offer this chart updated weekly by NOAA for Notices to Mariners and critical corrections. Charts are printed when ordered using Print-on-Demand technology. New Editions are available 5-8 weeks before their release as traditional NOAA charts. Ask your chart agent about Print-on-Demand charts or contact NOAA at 1-800-584-4863, http://NoceanGraftx.com, or help@NauticalCharts.gov, or OceanGrafix at 1-877-56CHART, http://OceanGrafix.com, or help@OceanGrafix.com.

MARINE WEATHER FORECASTS. NATIONAL WEATHER SERVICE

TELEPHONE NUMBER CITY

Tallahassee El (850) 942-8833

OFFICE HOURS 8:00 AM-5:00 PM (Mon.-Fri.)

BROADCASTS OF MARINE WEATHER FORECASTS AND WARNINGS BY MARINE RADIOTELEPHONE STATIONS CITY STATION FREQ. BROADCAST TIMES-CST SPE

SPECIAL WARNING Mobile, Ala WLO

FREQ. 2572 kHz 8808.8 kHz 4397.7 kHz

13178.8 kHz

6:00 AM, 7:00 PM, & Midnight

On receipt

22707.6 kHz

(Ch 25) 161.85 MHz (Ch 26) 161.90 MHz (Ch 27) 161.95 MHz

6:00 & 11:00 AM 5:00 & 11:00 PM

(Ch 28) 162.0 MHz

St Petersburg, Fla NMA-21

8:20 AM & 7:20 PM 2670 kHz

\*On receipt \*On receipt

Panama City, Fla


157.1 MHz

4:00 AM & 6:00 PM 3:05 AM, 3:05, 5:05, & 9:05 PM 4:36 & 10:35 AM, 4:35 PM

\*Preceded by announcement on 2182 kHz and 156.8 MHz

1000 0

Distress calls for small craft are made on 2182 kHz or channel 16 (156.80 MHz) VHF.



Yards

2000

3000

4000

5000



NO	VEMBE	R 2005		DE	CEVE	ER 2005			ANI IAS	RY 2006		FFF	SEN IAS	Y 2006	
Time	HL.	Time	Ht.	Time	Ht	Time	Ht.	Time	Ht.	Time	Ht.	Time	Ht.	Time	Ht.
Day h.m.	ft.	Day h.m.	ft.	Day h.m.	ft.	Dey h.m.	ft.	Day h.m.	ft.	Day h.m.	f 1.	Day h.m.	ft.	Day hyn.	ft.
I 0013 Tu 0730 1414 1856	2.3 0.0 1.9 1.3	16 0022 W 0619 1549 1836	2.6 -0.5 1.5 1.4	0803 Th	-0.8	16 0027 F 0855	2.5	I 0110 Su 0935 1733 1941	2.6 -1.0 1.2	16 0152 M 0946 1646 2033	2.1 -0.5 1.1 6.8	I 0317 W 1018 1643 2221	2.0 -0.3 1.5 0.3	16 0319 Th 0949 1555 2208	1.7 0.0 1.6 0.2
2 0032 W 0809 1506 1912	2.5 -0.2 1.9 1.4	17 0049 Th 0901	2.7 -0.5	2 0024 F 0050	-0.7	17 0105 Se 0934	-0.6	2 0207 M 1019 1746 2056	2.5 -0.8 1.2	17 0236 Tu 1014 1655 2127	2.0 -0.4 1.2 0.7	2 0420 Th 1045 1705 2326	1.7 0.0 1.7 0.1	17 0408 F 1009 1614 2256	0.2 1.7 0.0
3 0055 Th 0851 1609 1925	2.6 -0.3 1.7 1.5	18 01 19 F 0944	2.7	3 DIOS Se 0940	-0.7	18 0146 St 1014	2.4 -0.5	3 0307 Tu 1100 1803 2215	2.3 -0.6 1.3 0.9	18 0323 W 1040 1710 2223	1.9 -0.2 1.3 0.6	3 0528 F 1105 1732	1.3 0.3 1.9	18 0503 Se 1025 1637 2350	1.3 D.4 1.9 -0.1
4 0125 F 0939 1727 1935	2.7 -0.3 1.6 1.5	19 0154 Sa 1030	2.6 -0.3	4 0155 Su 1034	-0.7	19 0233 M 1052 1828 2106	2.3 -0.4  .2  .1	4 0412 W 1137 1823 2335	2.1 0.3 1.5 0.7	19 0414 Th 1106 1729 2321	1.7 0.0 1.5 0.5	4 0042 Se 0851 1113 1803	-0.1 1.0 0.8 2.0	19 0809 Su 1035 1704	1.1 0.7 2.0
5 0203 Sn 1033	2.8 -D.3	20 0236 Su 1121	2.5 -0.2	5 0252 M 1128	2.6 -0.5	20 0324 Tu 1131 1044 2221	-0.3  -3  -1	5 0523 Th 1210 1040	0.D 1.B	20 0511 F 1129 1751	1.4 0.2 1.6	5 0204 Su 1841	-0.2 2.1	20 0057 M 0747 1025 1736	0.9 0.8 0.8 2.0
6 0249 Su 1136	2.8 -0.3	21 0327 H 1214	2:4 0:0	6 0358 Tu 1222 2003 2310	2.4 -0.4 1.4	21 0420 W 1238 1904 2341	1.9 -0.1 1.4 1.6	6 0100 F 0843 1240 1917	0.4 1.3 0.4 1.6	21 0026 Se 0519 1149 1816	0.3 1.2 0.5 1.7	6 0334 M 1929	-0.4 2.1	21 0219 Tu 1821	-0.2 2.1
7 0347 M 1245	2.7 -0.2	22 0429 Tu 130B 2107 2333	2.2 0.1 1.4 1.3	7 D514 W 1313 2025	2.1 -0.1 1.5	22 0523 Tr 1245 1927	1.7 0.1 1.5	7 0228 5e 0831 1302 1951	0.1 1.0 0.7 2.0	22 0137 Su 0747 1159 1845	0.1 1.0 0.7 1.8	7 0458 Tu 2034	-0.5 2.0	22 0346 W 1928	-0.4 2.1
0 0501 Tu 1355	2.5 -0.1	23 0545 W 1400 2122	2.0 0.2 1.5	8 0103 Th 0642 1401 2051	1.8 0.2	23 0105 F 0636 1321 1952	0.8 1.4 0.3 1.6	8 0352 Su 2031	2.1	23 0254 M 1921	-0.1 1.9	6 0602 W 2150	-0.6 2.0	23 0504 Th 2057	-0.6 2.1
9 0635 W 1458 2227	2.2 D.1 1.7	24 0140 Th 0719 1447 2140	1.8 0.4 1.6	9 0242 F 0824 1444 2118	0.7 0.5 1.9	24 0228 50 0805 1357 2019	0.6 0.6 1.7	9 0503 M 2117	-0.4 2.2	24 0411 Tu 2011	-0.3	9 0651 Th 2300	-0.7 2.0	24 0604 F 2221	-0.8 -0.8
10 0240 Th 0820 1551 2242	1.4 2.0 0.3 1.8	25 0310 F 0848 1529 2157	1.6 0.5 1.7	10 0405 Sa 1019 1522 2147	0.3 1.3 0.8 2.1	25 0338 St 0956 1432 2049	0.3 1.1 8.0 1.9	10 0606 Tu 2207	-0.6 2.2	25 0519 W 2114	-0.8 2.1	ID 0729 F 2353	-0.7 2.1	25 0652 Se 1437 1721 2332	-0.9 1.2 1.1 2.3
II 0407 F 1002 1634 2259	1.0 1.9 0.5 2.0	26 0417 Se 1021 1607 2215	0.7 1.5 U.7 1.9	11 0511 Su 1204 1557 2217	0.D 1.3 1.0 2.2	25 0440 M 1157 1505 2122	0.0 1.1 1.0 2.0	11 0856 W 2257	2.2	28 0619 Th 2221	-0.8 2.3	11 0800 Se 1524 1822	3.6-  .  U.I	28 0732 Su 1436 1827	-0.9 1.2 0.9
12 0512 Sa 1128 1709 2318	0.5 1.8 0.8 2.2	27 G510 Su 1139 1840 2231	0.4 1.5 0.9 2.0	12 5606 M 1332 1627 2248	-0.4 1.3 1.2 2.4	27 0534 Tc 2159	·0.3	12 0739 Th 2344	-0.8 2.2	27 0710 F 2325	-1.0 2.4	12 0037 Su 0824 1523 1910	2.1 -0.6 1.1 0.8	27 0033 M 0868 1442 1926	2.3 -0.7 1.3 0.6

28 0755 -1.1 Se 1558 1.2 1801 1.1

1910 1.0
30 0121 2.5
M 0914 -0.9
1611 1.2
2013 0.7
31 0218 2.3
Tu 0948 -0.7
1625 1.2
2116 0.5

14 0028 2.2 29 0024 2.5 Se 0848 -0.7 29 0036 -1.0 1801 1.0 13 0116 2.0 M 0847 -0.4 1524 1.2 1955 0.7

14 0155 1.9 Tu 0808 -0.3 1528 1.3 2038 0.5

15 0235 1.8 W 0929 -0.2 1539 1.4 2122 0.3 28 0130 2.2 Tu 0837 -0.4 1454 1.5 2021 0.3

28 0555 0.0 9 1246 1.5 1708 1.1 2255 2.2

29 0837 -0.2 Tu 1348 1.5 1732 1.3 2320 2.4 30 0718 -0.5 W 1451 1.4 2349 2.8

2338 2.6 14 0653 -0.2 M 1344 1.7 1803 1.2 2359 2.5 15 0797 -0.4 Tu 1445 1.6 1823 1.3 13 0653 -0.6 Tu 1449 1.3 1652 1.2 2319 2.4


14 0736 -0.7 W 2352 2.5 28 0525 -0.5 W 2240 2.3

29 0714 -0.8 TF 2326 2.5


39 0002 -0.9

31 0016 2.6 Sa 0650 -1.0

1	WARCH	2006			- /	4PR I L	. 20	006				MAY	200	96
Time Day	Ht.	Time	Ht.	Jay	Time	Ht.	Di	Time	Ht.	D	Time	Ht.	Di	Time
h-m-	ft.	h.m.	H.		h.m.	ft.		h-m-	ft.	_	h.m.	Ft.		h-m-
1 0227 W 0904 1510 2117	2.0 -0.1 1.7 0.0	16 0235 Th 0839 1429 2109	1.7 0.3 1.8 0.0	1 0 Sn 0	448 838 458 256	1.3 1.0 2.5 -0.5	16 SL	0432 0810 1419 2224	1.4 1.1 2.5 -0.3	Ņ	1454 2340	2.6 -0.3	Tu	1435 2319
2 0326 Th 0927 1531 2213	1.7 0.2 1.9 -0.2	17 0320 F 0856 1447 2150	1.5 0.5 2.0 -0.1	2 0 Su 0	615 631 531 358	1.1 1.0 2.5 -0.4	N.	0547 0619 1454 2320	1.3 1.2 2.5 -0.3	Τü	154	2.5	17 W	1531
3 0429 F 0945 1556 2313	1,4 0.5 2.1 -0.3	18 0410 Se 0912 1510 2235	0.7 2.1 -0.2	3 I	610	2.4	TL	1538	2.5	3 W	0043 1637	-0.2 2.3	18 Th	00 IB 1636
4 0540 Sa 0954 1626	0.7 2.2	19 0509 Su 0924 1538 2328	0.8 2.2 -0.3	4 0 Tu i	111 659	-0.3 2.3	19	0027 1632	-0.3 2.5	Th	0148 1749	2.1	15	0117 1753
5 0019 Su 0721 0932 1700	-0.3 0.9 0.6 2.2	20 0625 M 0928 1609	1.0	5 Q	236 B06	-0.2 2.1	2Ú Tř	0142 1744	-0.3 2.3	5 F	0248 1916	2.0	20 Sa	0212 0942 1345 1922
6 0137 M 1742	-0.3 2.2	21 0035 Tu 165	-0.3	8 O Th I	354 944	-0.1 1.9	21 F	0254 1917	-0.3	6 Sa	0338 1112 1506 2052	0.2 1.5 1.3	21 Su	0301 0950 1522 2100
7 0311 Tu 1838	-0.3 2.1	22 0158 W 1749	-0.3 2.2	7 0 F 2	452 129	-0.1 1.9	22 8a	0355 1143 1514 2058	-0.2 1.5 1.3 2.1	7 Su	04 18 11 14 1626 2220	0.3 1.6 1.0 1.7	22 M	0344 1020 1639 2236
8 D437 W 2005	-0.4 2.0	23 0325 Th 1913	-0.4 2.2	8 0 Se 1 2	534 251 544 249	-0.1  .4  .1  .9	23 \$L	0445 1144 1638 2228	-0.1 1.6 1.0 2.0		0452 112 1723 233	0.5 1.8 0.7 1.7	Z3 Tu	0421 1043 1741
9 0540 Th 2147	-0,4 1.9	24 0438 F 2056	-0.5 2.2	9 0 90 1 2	805 248 741 346	0.0 1.5 0.9 1.9	24 M	0525 1155 1742 2345	0.1 1.0 0.5 1.9	οĘ	052 1129 1806	0.7 1.9 0.4	24 W	0008 0452 1106 1835
F 1421 1537 2303	-0.4 1.3 1.2 1.9	25 0533 Sm 1317 1526 2225	-0.5 1.4 1.2 2.2	10 0	629 250 826	0.2 1.8 0.6	25 Tu	0558 1239 1836	0.4 2.0 0.1	10	0030 0546 114 1849	1.6 0.9 2.1 0.1	25 Th	0124 0518 1134 1924
D656 Sa  410    1744    2356	-0.4 1.3 1.0 2.0	26 0616 Su 1313 1738 2337	-0.5 1.4 0.9 2.2	11.8	033 650 253 904	1.8 0.4 1.7 0.3	26 W	0052 0625 1226 1926	1.8 0.7 2.3 -0.2	Th	0124 0607 1158 1927	1.6 1.1 2.2 -0.1	26 F	0240 0536 1204 2011
12 0723 Su 1406 1932	-0.3 1.3 0.6	27 0652 M 1319 1836	-0.3 1.6 0.5	15 0	117 709 259 941	1.7 0.5 1.9 0.1	27 Th	0156 0648 1247 2014	1.7 0.9 2.5 0.4	12 F	0217 0625 1216 2006	1.5 1.2 2.4 0.2		1238 2058
13 D03B M D744 14CB 1914	2.0 -0.2 1.4 0.6	28 0040 Tu 0722 1330 1928	2.1 -0.1 1.7 0.1	13 0 Th 0	150 727 311 018	1.7 0.7 2.1	26 F	0301 0706 1312 2102	1.5 1,1 2.6 -0.5	13 Sə	0314 0637 124 2047	1.3 2.6 -0.4	29 Su	1312 2144
14 D117 Tu 09C2 14C9 1952	1.9 0.0 1.5 0.4	29 0139 Y 0748 1345 2019	2.0 0.3 2.0	14 0 F 0	244 743 329 055	1.8 0.9 2.2 -0.2	29 Sa	0413 0716 1341 2151	1.4 1.2 2.7 -0.5		042 0646 1312 2133	1.4 1.3 2.7 -0.4	29 M	1352 2231
15 D155 W 0621 1416 2031	1.8 0.2 1.6 0.2	30 0237 Th 0610 1405 2110	1.7 0.5 2.2 -0.4	15 0 5e 0	333 758 351 137	1.5 1.0 2.4 -0.3	30 54	1415 2243	2.7		1350 2224	2.7 -0.4	30 Tu	1437 2319
		31 0339 F 0628 1429 220	1.5 0.8 2.4 -0.5										31 W	1529



This BookletChart was reduced to 75% of the original chart scale. The new scale is 1:53333. Barscales have also been reduced and are accurate when used to measure distances in this BookletChart.



	T	_				
6 no Ht. n. ft		<del>.</del>				
1 0.6 5 1.7 7 0.9 8 2.0						
8 2.0 5 0.3 6 1.7 5 1.1 3 2.2	2228 2.4 2208 2.1 2 0608 -0.4 IT 0619 -0.3 5 6 1319 1.5 Su 1416 1.3 1650 1.2 1614 1.3 2 2300 2.5 2241 2.3					
3 2.2 4 0.0 0 1.7 9 1.2 1 2.3	2300 2.6 2241 2.5 3 0659 -0.7 18 0702 -0.5 50 1436 1.5 14 2515 2.3 1 713 1.4 2333 2.7					
9 1.2	1713 1.4 2333 2.7 4 0747 -0.8 13 0743 -0.6 M Tu 2353 2.6					
1 -0.1 9 1.4 2 2.4 8 -0.3 3 1.6 4 1.4						
7 2.5 7 -0.4 1 1.5 7 1.4	7 0131 2.7 22 0122 2.5					
7 2.6 9 -0.4						
4 2.6 5 -0.4	1810 1.3 2103 1.3	· !				
8 2.6	1934 1.3 1828 1.3 2134 1.2 2223 1.0					
Q -0.3	2315 1.2 2348 0.6					
4 2.4 4 0.2 2 1.5 0 1.4						
8 0.0 4 1.6	2024 1.6 1042 1.6	:				
9 1.2 1 1.9 8 0.2 8 1.7	13 0224 0.8 28 0242 0.2 W 0801 1.4 Th 0841 1.1 1419 0.6 1341 0.1 2047 1.7 2010 2.0					
3 0.9 1 1.7 4 0.5 3 1.9	H 14 0341 0.5 29 0401 -0.1 Th 0951 1.2 F 1107 1.0 1 1457 0.6 1407 0.5 2112 1.8 2055 2.2	<u>:</u>				
9 G.4 8 1.5 4 0.8 9 2.1						
	31 0610 -0.7 Su 2225 - 2.4					
						ے
	{		s <sup>s</sup> ,s			Jing.
1/26					, bì	<u>လုံ</u>
``````````````````````````````````````			48° , is		18th	
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			186 1,ti		8	page
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\					· · · · ·	page
186	Limitation	CALTION s on the use of radio signals as	PLANE COORDINATE GRID (based on NAD 1927)		,	
1.766	aids to marin U.S. Coast (	s on the use of radio signals as e navigation can be found in the Buard Light Lists and National	PLANE COORDINATE GRID	×	,	
116	aids to marin U.S. Coast ( Geospatial-Int Radio direc	s on the use of radio signals as e navigation can be found in the Auard Light Lists and National elligence Agency Publication 117. tion-finder bearings to commercial	PLANE COORDINATE GRID (based on NAD 1927) Florida State Grid, north zone, is indicated by doshed ticks at 10,000 foot intervals, thus	×	*	Low wooded area
	aids to marin U.S. Coast ( Geospatial-Int Radio direc broadcasting should be us	s on the use of radio signals as e navigation can be found in the Suard Light Lists and National elligence Agency Publication 117. tion-finder bearings to commercial stations are subject to error and ed with caution.	PLANE COORDINATE GRID (based on NAD 1927) Florida State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus: The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to	×		Low wooded area
	aids to marin U.S. Coast ( Geospatial-Irt Radio direc broadcasting should be us Station pos	s on the use of radio signals as e navigation can be found in the Buard Light Lists and National elligence Agency Publication 117. tion-finder boarings to commercial stations are subject to error and	PLANE COORDINATE GRID (based on NAD 1927) Florida State Grid, north zone, is indicated by dashed licks at 10,000 foot intervals, thus: The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.	*	*	Low wooded area
	aids to marin U.S. Coast ( Geospatial-Irt Radio direc broadcasting should be us Station pos	s on the use of radio signals as e navigation can be found in the bard Light Lists and National elligence Agency Publication 117. tion-finder boarings to commercial stations are subject to error and et with caution.	PLANE COORDINATE GRID (based on NAD 1927) Florida State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus.—  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.  CAUTION For bascule bridges, whose spans do not	. *		Low wooded area
	aids to marin U.S. Coast ( Geospatial-Irt Radio direc broadcasting should be us Station pos	s on the use of radio signals as e navigation can be found in the bard Light Lists and National elligence Agency Publication 117. tion-finder boarings to commercial stations are subject to error and et with caution.	PLANE COORDINATE GRID (based on NAD 1927) Florida State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus:  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning olds to navigation.  CAUTION For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is	*	White (	Low wooded area  Surfaced Ramp
	aids to marin U.S. Coast ( Geospatial-Irt Radio direc broadcasting should be us Station pos	s on the use of radio signals as e navigation can be found in the bard Light Lists and National elligence Agency Publication 117. tion-finder boarings to commercial stations are subject to error and et with caution.	PLANE COORDINATE GRID (based on NAD 1927) Florido State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus.— The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.  CAUTION For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire	×.		Low wooded area  Surfaced Ramp  City  Fixe Biblore Hor Class FT
1.46	aids to marin U.S. Coast ( Geospatial-Irt Radio direc broadcasting should be us Station pos	s on the use of radio signals as e navigation can be found in the bard Light Lists and National elligence Agency Publication 117. tion-finder boarings to commercial stations are subject to error and et with caution.	PLANE COORDINATE GRID (based on NAD 1927) Florida State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus: The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.  CAUTION For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans	×.		Low wooded area  Surfaced Ramp
1.46	aids to marin U.S. Coast ( Geospatial-Irt Radio direc broadcasting should be us Station pos	s on the use of radio signals as e navigation can be found in the bard Light Lists and National elligence Agency Publication 117. tion-finder boarings to commercial stations are subject to error and et with caution.	PLANE COORDINATE GRID (based on NAD 1927) Florida State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus: The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.  CAUTION For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans	×	White (	Low wooded area  Surfaced Ramp  City  Fixe Biblore Hor Class FT
1.46	aids to marin U.S. Coast ( Geospatial-Irt Radio direc broadcasting should be us Station pos	s on the use of radio signals as e navigation can be found in the bard Light Lists and National elligence Agency Publication 117. tion-finder boarings to commercial stations are subject to error and et with caution.	PLANE COORDINATE GRID (based on NAD 1927) Florida State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus: The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.  CAUTION For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans	*	White (	Low wooded area  Surfaced Ramp  City  Fixe Bibliote Hori Cl. 200 FT Heri Cl. 66 FT
186	aids to marin U.S. Coast ( Geospatial-Irt Radio direc broadcasting should be us Station pos	s on the use of radio signals as e navigation can be found in the bard Light Lists and National elligence Agency Publication 117. tion-finder boarings to commercial stations are subject to error and et with caution.	PLANE COORDINATE GRID (based on NAD 1927) Florido State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus.— The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.  CAUTION For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans over the channel.	×.	White (	Low wooded area  Surfaced Ramp  City  Free bullote Free Class FT
	aids to marin U.S. Coast ( Geospatial-Int Radio direc broadcasting should be us Station pos ⊙(Accurate Id	s on the use of radio signals as as enavigation can be found in the Buard Light Lists and National elligence Agency Publication 117.  Into-finder boarings to commercial stations are subject to error and ad with caution.  Itions are shown thus:  ccation) o(Approximate location)	PLANE COORDINATE GRID (based on NAD 1927) Florido State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus.— The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.  CAUTION For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted florizontal clearance when the bridge is open, due to the inclinations of the drawspans over the channel	*	White (	Low wooded area  Surfaced Ramp  City  Free bullote Free Class FT
	aids to marin U.S. Coast ( Geospatial-Int Radio direc broadcasting should be us Station pos ⊙(Accurate Id	s on the use of radio signals as as enavigation can be found in the Buard Light Lists and National elligence Agency Publication 117.  Into-finder boarings to commercial stations are subject to error and ad with caution.  Itions are shown thus:  ccation) o(Approximate location)	PLANE COORDINATE GRID (based on NAD 1927) Florido State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus.— The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.  CAUTION For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans over the channel.	×	White (	Low wooded area  Surfaced Ramp  City  Free bullote Free Class FT
	aids to marin U.S. Coast ( Geospatial-Int Radio direc broadcasting should be us Station pos ⊙(Accurate Id	s on the use of radio signals as as enavigation can be found in the Buard Light Lists and National elligence Agency Publication 117.  Into-finder boarings to commercial stations are subject to error and ad with caution.  Itions are shown thus:  ccation) o(Approximate location)	PLANE COORDINATE GRID (based on NAD 1927) Florida State Grid, north zone, is indicated by doshed ticks at 10,000 toot intervals, thus: The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning olds to navigation.  CAUTION For bascule bridges, whose spars do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans over the channel	×.	White (	Low wooded area  Surfaced Ramp  City  FIXED BRIDGE HOPT CL. 200 FT VERT CL. 60 FT
	aids to marin U.S. Coast ( Geospatial-Int Radio direc broadcasting should be us Station pos ⊙(Accurate Id	s on the use of radio signals as as enavigation can be found in the Buard Light Lists and National elligence Agency Publication 117.  Into-finder boarings to commercial stations are subject to error and ad with caution.  Itions are shown thus:  ccation) o(Approximate location)	PLANE COORDINATE GRID (based on NAD 1927) Florido State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus.— The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.  CAUTION For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted florizontal clearance when the bridge is open, due to the inclinations of the drawspans over the channel	*	White (	Low wooded area  Surfaced Ramp  City  FIXED BRIDGE HOPT CL. 200 FT VERT CL. 60 FT
	aids to marin U.S. Coast ( Geospatial-Int Radio direc broadcasting should be us Station pos ⊙(Accurate Id	s on the use of radio signals as as enavigation can be found in the Buard Light Lists and National elligence Agency Publication 117.  Into-finder boarings to commercial stations are subject to error and ad with caution.  Itions are shown thus:  ccation) o(Approximate location)	PLANE COORDINATE GRID (based on NAD 1927) Florado State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus: The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning olds to navigation.  CAUTION For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans over the channel.	×	White (	Low wooded area  Surfaced Ramp  City  FIXED BRIDGE HOPT CL. 200 FT VERT CL. 60 FT
	aids to marin U.S. Coast ( Geospatial-Int Radio direc broadcasting should be us Station pos ⊙(Accurate Id	s on the use of radio signals as a vigation can be found in the Buard Light Lists and National elligence Agency Publication 117.  Into-finder boarings to commercial stations are subject to error and ad with caution, litions are shown thus: coation)  o(Approximate location)	PLANE COORDINATE GRID (based on NAD 1927) Florida State Grid, north zone, is indicated by doshed ticks at 10,000 toot intervals, thus: The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning olds to navigation.  CAUTION For bascule bridges, whose spars do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans over the channel	Low swampy area	White (	Low wooded area  Surfaced Ramp  City  FIXED BRIDGE HOPT CL. 200 FT VERT CL. 60 FT
	aids to marin U.S. Coast ( Geospatial-Int Radio direc broadcasting should be us Station pos ⊙(Accurate Id	s on the use of radio signals as a vigation can be found in the Buard Light Lists and National elligence Agency Publication 117.  Into-finder boarings to commercial stations are subject to error and ad with caution, litions are shown thus: coation)  o(Approximate location)	PLANE COORDINATE GRID (based on NAD 1927) Florido State Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.  CAUTION For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans over the channel.  The Klink  Obsta FA  CAUTION CAUT	Low swampy area	White (	Low wooded area  Surfaced Ramp  City  Fixed Bridge Mon of 200 FT Men of
	aids to marin U.S. Coast ( Geospatial-Int Radio direc broadcasting should be us Station pos ⊙(Accurate Id	s on the use of radio signals as a vigation can be found in the Buard Light Lists and National elligence Agency Publication 117.  Into-finder boarings to commercial stations are subject to error and ad with caution, litions are shown thus: coation)  o(Approximate location)	PLANE COORDINATE GRID (based on NAD 1927) Florida State Grid, north zone, is indicated by doshed tics at 10,000 toot intervals, thus: The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning olds to navigation.  CAUTION For bascule bridges, whose spars do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans over the channel	Low swampy area FION s or defects in aids to aled on this chart. See	White (	Low wooded area  Surfaced Ramp  FixeD BRIDGE HOR CL 200 FT VERT CL 85 FT
	aids to marin U.S. Coast ( Geospatial-Int Radio direc broadcasting should be us Station pos ⊙(Accurate Id	s on the use of radio signals as a vigation can be found in the Buard Light Lists and National elligence Agency Publication 117.  Into-finder boarings to commercial stations are subject to error and ad with caution, litions are shown thus: coation)  o(Approximate location)	PLANE COORDINATE GRID (based on NAD 1927) Florado State Grid, north zone, is indicated by doshed ticks at 10,000 foot intervals, thus: The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.  CAUTION For bascule bridges, whose spars do not open to a full vertical position, unlimited overhead clearance is not available for the entire charted forizontal clearance when the bridge is open, due to the inclinations of the drawspans over the channel  Temporary change mavigation are not indicated to supplementations of the drawspans over the channel supplementations of the drawspans over the channel supplementation of the drawspans over the channel su	Low swampy area  FION s or defects in aids to alted on this chart. See Soon by broken lines are	White (	Low wooded area  Surfaced Ramp  City  Fixed Bridge Mon of 200 FT Men of
	aids to marin U.S. Coast ( Geospatial-Int Radio direc broadcasting should be us Station pos ⊙(Accurate Id	s on the use of radio signals as a vigation can be found in the Buard Light Lists and National elligence Agency Publication 117.  Into-finder boarings to commercial stations are subject to error and ad with caution, litions are shown thus: coation)  o(Approximate location)	PLANE COORDINATE GRID (based on NAD 1927) Florido Stote Grid, north zone, is indicated by dashed ticks at 10,000 foot intervals, thus: The last three digits are omitted.  AIDS TO NAVIGATION Consult U.S. Coast Guard Light List for supplemental information concerning oids to navigation.  CAUTION For bascule bridges, whose spans do not open to a full vertical position, unlimited overhead clearance is not available for the entitie charted horizontal clearance when the bridge is open, due to the inclinations of the drawspans over the channel.  Alarrison Swamp The Kink  Obsenta  CAUTION  Temporary change navigation are not indicated to the inclinations of the drawspans over the channel indicated to the inclinations of the drawspans over the channel indicated to Maniner to the coal Notice to Maniner	Low swampy area  FION s or defects in aids to alted on this chart. See Soon by broken lines are	White (	Low wooded area  Surfaced Ramp  City  Fixed Bridge Mon of 200 FT Men of



PORT ST. JOE HARBOR CHANNEL DEPTHS

CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER Joins page 13




FACILITIES

Locations of public marine facilities are shown by large magenta numbers with leaders and refer to the facility tabulation.

/	DEPTH			SERVIC					$\overline{}$		JPPLIE:		\					
NO	AND A COLCULAR OF THE AND A COLCULATION	A SUN	MARIN STULL VA	LIFT C. CAIL MATORIFIE	SORCII LEEF SOIO	BOAT RENTA CANO	CHARLA	TOR TOR	Comp. Comp.	Notes STATES AND	MATERIAL PROPERTY AND PARTY AND PART	POCE PIES	OKSK AROM.	ON SER	SASON	W.	\	\
_	PRESNELL'S BAYSIDE M	3	3	В	s	HMR			СМ	c	FC	тѕ	WD	c	W	GH	вт	
3																		
4	HIDE-A-WAY HARBOR	6	6	ВЕ	S						FL	T	W		WI	GH	ВТ	DG
-	HIDE-A-WAY HARBOR MEXICO BCH.CANL PK	6 5	6 5	B E	S S				М	С	FL FLC	T P	WD	С	WI	GH GH	BT BT	D G

THE LOCATIONS OF THE ABOVE PUBLIC MARINE FACILITIES ARE SHOWN ON THE CHART BY LARGE MAGENTA NUMBERS. THE TABILATED "APPROACH-FEET(REPORTED" IS THE DEPTH AVAILABLE FROM THE NEAREST NATURAL OR DREDGED CHANNEL TO THE TABILATED" PUMPING STATION'S DEFINED AS FACILITIES AVAILABLE FOR PUMPING OUT BOAT HOLDING TANKS.



1000 0

Yards

2000

3000

4000

5000

1000





# LAKE WIMICO TO EAST BAY

) THE FACILITY




Chart 11393 21st Ed., Nov. /05 ■
Corrected through NM Nov. 12/05, LMM Nov. 08/05
Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

MERCATOR PROJECTION, SCALE 1:40,000 AT LAT. 29°50' SOUNDINGS IN FEET AT MEAN LOWER LOW WATER NORTH AMERICAN DATUM OF 1983 (WORLD GEODETIC SYSTEM 1984)

Additional information can be obtained at nauticalcharts.noaa.gov.

HEIGHTS


Heights in feet above Mean High Water.


AUTHORITIES


Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, and L.S. Coast Guard.

SUPPLEMENTAL INFORMATION
Consult U.S. Coast Pilot 5 for important supplemental information.

Joins page 15\_











Yards


1000 0



























## **EMERGENCY INFORMATION**

#### VHF Marine Radio channels for use on the waterways:

Channel 6 – Inter-ship safety communications.

**Channel 9** – Communications between boats and ship-to-coast.

**Channel 13** – Navigation purposes at bridges, locks, and harbors.

#### Channel 16 – Emergency, distress and safety calls

to Coast Guard and others, and to initiate calls to other vessels. Contact the other vessel, agree to another channel, and then switch.

**Channel 22A** – Calls between the Coast Guard and the public. Severe weather warnings, hazards to navigation and safety warnings are broadcast here.

Channels 68, 69, 71, 72 & 78A – Recreational boat channels.

#### **Distress Call Procedures**

- 1. Make sure radio is on.
- 2. Select Channel 16.
- 3. Press/Hold the transmit button.
- 4. Clearly say: "MAYDAY, MAYDAY, MAYDAY."
- Also give: Vessel Name and/or Description; Position and/or Location; Nature of Emergency; Number of People on Board.
- 6. Release transmit button.
- Wait for 10 seconds If no response Repeat MAYDAY Call.

#### HAVE ALL PERSONS PUT ON LIFE JACKETS!!

**Mobile Phones** – Call 911 for water rescue.

Coast Guard Group Mobile – 251-441-6211 Coast Guard Panama City – 850-234-2475 FL Fish and Wildlife Conservation Comm – 888-404-3922

Coast Guard Atlantic Area Cmd - 757-398-6390

<u>NOAA Weather Radio</u> – 162.400 MHz, 162.425 MHz, 162.450 MHz, 162.475 MHz, 162.500 MHz, 162.525 MHz, 162.550 MHz.

Getting and Giving Help – Signal other boaters using visual distress signals (flares, orange flag, lights, arm signals); whistles; horns; and on your VHF radio. You are required by law to help boaters in trouble. Respond to distress signals, but do not endanger yourself.



# NOAA CHARTING PUBLICATIONS

Official NOAA Nautical Charts – NOAA surveys and charts the national and territorial waters of the U.S, including the Great Lakes. We produce over 1,000 traditional nautical charts covering 3.4 million square nautical miles. Carriage of official NOAA charts is mandatory on the commercial ships that carry our commerce. They are used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters. NOAA charts are available from official chart agents listed at: <a href="https://www.NauticalCharts.NOAA.gov">www.NauticalCharts.NOAA.gov</a>.

Official Print-on-Demand Nautical Charts – These full-scale NOAA charts are updated weekly by NOAA for all Notice to Mariner corrections. They have additional information added in the margin to supplement the chart. Print-on-Demand charts meet all federal chart carriage regulations for charts and updating. Produced under a public/private partnership between NOAA and OceanGrafix, LLC, suppliers of these premium charts are listed at <a href="https://www.oceanGrafix.com">www.oceanGrafix.com</a>.

## Official Electronic Navigational Charts (NOAA ENCs®) –

ENCs are digital files of each chart's features and their attributes for use in computer-based navigation systems. ENCs comply with standards of the International Hydrographic Organization. ENCs and their updates are available for free from NOAA at www.NauticalCharts.NOAA.gov.

## Official Raster Navigational Charts (NOAA RNCs<sup>™</sup>) –

RNCs are geo-referenced digital pictures of NOAA's charts that are suitable for use in computer-based navigation systems. RNCs comply with standards of the International Hydrographic Organization. RNCs and their updates are available for free from NOAA at <a href="https://www.NauticalCharts.NOAA.gov">www.NauticalCharts.NOAA.gov</a>.

Official BookletCharts<sup>™</sup> – BookletCharts<sup>™</sup> are reduced scale NOAA charts organized in page-sized pieces. The "Home Edition" can be downloaded from NOAA for free and printed. The Internet address is <a href="https://www.NauticalCharts.gov/bookletcharts">www.NauticalCharts.gov/bookletcharts</a>.

Official PocketCharts<sup>TM</sup> – PocketCharts<sup>TM</sup> are for beginning recreational boaters to use for planning and locating, but not for real navigation. Measuring a convenient 13" by 19", they have a 1/3 scale chart on one side, and safety, boating, and educational information on the reverse. They can be purchased at retail outlets and on the Internet.

Official U.S. Coast Pilot® – The Coast Pilots are 9 text volumes containing information important to navigators such as channel descriptions, port facilities, anchorages, bridge and cable clearances, currents, prominent features, weather, dangers, and Federal Regulations. They supplement the charts and are available from NOAA chart agents or may be downloaded for free at <a href="https://www.NauticalCharts.NOAA.gov">www.NauticalCharts.NOAA.gov</a>.

Official On-Line Chart Viewer – All NOAA nautical charts are viewable here on-line using any Internet browser. Each chart is up-to-date with the most recent Notices to Mariners. Use these on-line charts as a ready reference or planning tool. The Internet address is www.NauticalCharts.gov/viewer.

Official Nautical Chart Catalogs – Large format, regional catalogs are available for free from official chart agents. Page size, state catalogs are posted on the Internet and can be printed at home for free. Go to <a href="http://NauticalCharts.NOAA.gov/mcd/ccatalogs.htm">http://NauticalCharts.NOAA.gov/mcd/ccatalogs.htm</a>.

Internet Sites: <a href="https://www.Noa.gov">www.Noa.gov</a>, <a href="